

1544G Blue Sprue

	Section 1 Identification				
1.1 Product identifier	S				
	1544G Blue Sprue				
	d uses of the substance or mixture and uses advised against				
Identified uses	-				
1.3 Details of the supp	plier of the safety data sheet				
	ifacturing and Supply Company				
	oad, Avon, OH 44011				
(440) 934-190					
www.freemans	supply.com CHEMTREC (800) 424-9300				
	Section 2 Hazards Identification				
	ie substance or mixture				
	according to OSHA 29 CFR 1910.1200 HCS				
	ts, including precautionary statements				
No label eleme					
2.3 Hazards not other					
Molten produc	t can cause serious burns.				
	Section 3 Composition/Information on Ingredients				
3.1 Mixture of Substan					
	Proprietary mixture of waxes, resin(s), and oil soluble dye(s).				
No component	s need to be disclosed according to the applicable regulations.				
	Section 4 First Aid Measures				
4.1 Description of firs	t aid measures				
Inhalation	Get medical assistance if irritation develops or persists. If breathing is difficult,				
	move the person to fresh air. Give artificial respiration if person is not breathing.				
Skin contact	For thermal burns, flush or submerge effected area in cold water to dissipate heat.				
	Cover with clean bandage material. Do not peel material from skin. Get medical attention.				
	For contact at ambient temperatures, wash with soap and water.				
Eye contact	Immediately flush with plenty of water for at least 15 minutes.				
	If irritation persists, get medical attention immediately.				
Ingestion	If swallowed, rinse mouth with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Consult a physician if necessary.				
	Do No i muuce vointeing. Consult a physician n necessary.				
	Section 5 Fire Fighting Measures				
F 1 Extinguishing may	lia				
5.1 Extinguishing med	guishing media: Water fog, dry chemical, foam, carbon dioxide.				
	tinguishing media: Do not use a solid water stream as it may scatter and spread fire. Tising from the substance or mixture				
-	and Explosion Hazards: Molten material can create slippery conditions. Avoid generating dust; fine				
	in air in sufficient concentrations, and in the presence of an ignition source is a potential dust				
	rd. This is an unlikely scenario but users should be aware of the risk.				
	mbustion Products: Carbon dioxide, carbon monoxide, complex hydrocarbons, irritating smoke.				
5.3 Advice for firefigh					
	ained breathing apparatus for firefighting if necessary.				
Wear Sen cont	amea or eaching apparatus for monghting it necessary.				

	Section 6 Accidental Release Measur	res		
5.1 Personal precautions. protective	e equipment and emergency procedures			
Avoid breathing fumes. Avoid contact with skin and eyes. Wear appropriate personal protective equipment.				
.2 Environmental precautions				
	e environment. Prevent product from enter	ring drains.		
.3 Methods and materials for conta				
	Contain spillage and use clean non-sparkin	ng tools to collect material.		
Shovel spillage into suitable co	ontainer for disposal.			
	Section 7 Handling and Storage			
.1 Precautions for safe handling				
	rotective equipment Avoid contact with ski	n and eyes. Wash thoroughly with soap and		
		t use in areas without adequate ventilation.		
Avoid breathing fumes. Avoid		· ··· · ··· · · · · · · · · · · · · ·		
		nal investment casting process (except dew		
	product stand unused in melt tanks and in			
.2 Conditions for safe storage, inclu		•		
	s in closed containers. Keep away from igni	tion sources, heat, open flames, and direct		
sunlight. Do not heat above fla	ash point. This material can catch fire if over			
materials: strong oxidizing age	ents.			
S	ection 8 Exposure Controls/Personal Pro	otection		
1 Control parameters Exposure Limits/Guideline				
	Exposure Limit	Sources		
Exposure Limits/Guideline	Exposure Limit 2 mg/m ³ TWA	Sources NIOSH REL / ACGIH TLV		
Exposure Limits/Guideline Substance Name Wax fumes				
Exposure Limits/Guideline Substance Name Wax fumes	2 mg/m ³ TWA			
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us	NIOSH REL / ACGIH TLV		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstance	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes Substance Name Wax fumes Suppose controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment Eye/Face	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles.	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glow	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering con Good general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glove Skin/Body	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering conditions. Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glower Skin/Body Prevent skin contact, wear longer	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering cond Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glove Skin/Body Prevent skin contact, wear long Respiratory	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o ees, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering cond Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glove Skin/Body Prevent skin contact, wear long Respiratory The need for respiratory protection	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct.		
Exposure Limits/Guideline Substance Name Wax fumes 2 Exposure controls Appropriate engineering cond Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. 3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glove Skin/Body Prevent skin contact, wear lon Respiratory The need for respiratory protects If elevated airborne concentra	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of tions above applicable workplace exposure	NIOSH REL / ACGIH TLV eed. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct.		
Exposure Limits/Guideline Substance Name Wax fumes Wax fumes S.2 Exposure controls Appropriate engineering conditions Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. S.3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glow Skin/Body Prevent skin contact, wear londer Respiratory The need for respiratory protection If elevated airborne concentrated purifying respirator. Follow the	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use o	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct.		
Exposure Limits/Guideline Substance Name Wax fumes Wax fumes S.2 Exposure controls Appropriate engineering conditions Good general ventilation (typing to conditions. Supplementary needed in special circumstance dusts, etc. S.3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glow Skin/Body Prevent skin contact, wear londer Respiratory The need for respiratory protection If elevated airborne concentrated purifying respirator. Follow the	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of tions above applicable workplace exposure ne OSHA respirator regulations found in 29	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct.		
Exposure Limits/Guideline Substance Name Wax fumes Wax fumes Controls Appropriate engineering conditions Good general ventilation (typint to conditions. Supplementary needed in special circumstance dusts, etc. Wear safety glasses equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glow Skin/Body Prevent skin contact, wear lond Respiratory The need for respiratory protects If elevated airborne concentratora purifying respirator. Follow th 149. Use a NIOSH/MSHA or Eu	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of tions above applicable workplace exposure ne OSHA respirator regulations found in 29	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct.		
Substance NameWax fumesB.2 Exposure controlsAppropriate engineering colGood general ventilation (typito conditions. Supplementaryneeded in special circumstancdusts, etc.8.3 Personal protective equipmentEye/FaceWear safety glasses equippedHandsWear thermally resistant glowSkin/BodyPrevent skin contact, wear lonRespiratoryThe need for respiratory protectIf elevated airborne concentrapurifying respirator. Follow th149. Use a NIOSH/MSHA or Eusymptoms are experienced.Safety Stations	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of tions above applicable workplace exposure ne OSHA respirator regulations found in 29	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct. conditions and with adequate ventilation. e levels are anticipated, use an air- CFR 1910.134 or European Standard EN ator if exposure limits are exceeded or		
Exposure Limits/GuidelineSubstance NameWax fumesSubstance NameWax fumesSubstance NameAppropriate engineering colGood general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.Substance Appropriate engineering colGood general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.Substance Appropriate engineering colGood general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.Substance Appropriate engineering colAppropriate engineering colAppropriate engineering colGood general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.Substance Appropriate engineering colMake mergency engineering colMake emergency engineering colMake emergency engineering colMake emergency engineering colMake emergency engineering colSubstance Appropriate engineering colSkin/BodyPrevent skin contact, wear lonRespiratoryThe need for respiratory protectIf elevated airborne concentra purifying respirator. Follow the 149. Use a NIOSH/MSHA or Eu symptoms are experienced.Safety Stations	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of tions above applicable workplace exposure ne OSHA respirator regulations found in 29 uropean Standard EN 149 approved respirations tions and washing facilities available in work	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct. conditions and with adequate ventilation. e levels are anticipated, use an air- CFR 1910.134 or European Standard EN ator if exposure limits are exceeded or rk area.		
Exposure Limits/GuidelineSubstance NameWax fumes2 Exposure controlsAppropriate engineering colGood general ventilation (typi to conditions. Supplementary needed in special circumstanc dusts, etc.3 Personal protective equipment Eye/Face Wear safety glasses equipped Hands Wear thermally resistant glove Skin/Body Prevent skin contact, wear lon Respiratory The need for respiratory protect If elevated airborne concentrate purifying respirator. Follow that 149. Use a NIOSH/MSHA or Eusymptoms are experienced. Safety Stations Make emergency eyewash state General Hygienic Practices Avoid breathing dust, vapor or	2 mg/m ³ TWA ntrols cally 10 air changes per hour) should be us local exhaust ventilation, closed systems, o res, such as poorly ventilated spaces, very h with side shields, or safety goggles. es and long sleeves if handling molten prod ng sleeves and/or coveralls. ection is not anticipated under normal use of ations above applicable workplace exposure the OSHA respirator regulations found in 29 uropean Standard EN 149 approved respira	NIOSH REL / ACGIH TLV red. Ventilation rates should be matched r respiratory and eye protection may be ot processing, mechanical generation of luct. conditions and with adequate ventilation. e levels are anticipated, use an air- CFR 1910.134 or European Standard EN ator if exposure limits are exceeded or rk area. move contaminated clothing promptly and		

Section 9 Phy	sical and Chemical Properties
9.1 Information on basic physical and chemical pro	perties
Physical State:	Solid
Color:	Blue
Odor:	Mild
Odor Threshold:	No data available
pH:	Not applicable
Melting Point:	Approximately 151°F (66°C)
Boiling Point:	No data available
VOC Content:	0
Flash Point:	>365°F (185°C)
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Lower Explosion Limit:	No data available
Upper Explosion Limit:	No data available
Vapor Density:	No data available
Specific Gravity:	0.9 ± 0.5
Water Solubility:	Insoluble
Partition Coefficient: n-octanol/water:	No data available
Auto-Ignition Temperature:	No data available
Viscosity:	Solid at room temperature
Explosive Properties:	Not explosive
Oxidizing Properties:	Not an oxidizer
Section 1	0 Stability and Reactivity
10.1 Reactivity:	No dangerous reaction known under conditions of normal use.
0.1 Reactivity: 10.2 Chemical stability:	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions.
0.1 Reactivity: 0.2 Chemical stability: 10.3 Possibility of hazardous reactions:	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid:	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation.
0.1 Reactivity: 0.2 Chemical stability: 0.3 Possibility of hazardous reactions: 0.4 Conditions to avoid: 0.5 Incompatible materials:	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials:	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available
0.1 Reactivity: 0.2 Chemical stability: 0.3 Possibility of hazardous reactions: 0.4 Conditions to avoid: 0.5 Incompatible materials: 0.6 Hazardous decomposition products Section 11 1.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact
0.1 Reactivity: 0.2 Chemical stability: 0.3 Possibility of hazardous reactions: 0.4 Conditions to avoid: 0.5 Incompatible materials: 0.6 Hazardous decomposition products Section 11 1.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met
0.1 Reactivity: 0.2 Chemical stability: 0.3 Possibility of hazardous reactions: 0.4 Conditions to avoid: 0.5 Incompatible materials: 0.6 Hazardous decomposition products Section 11 1.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met Classification criteria not met
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 1.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b IARC, NTP, or OSHA.
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity Specific Target Organ Toxicity (STOT)	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b IARC, NTP, or OSHA. Classification criteria not met
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity Specific Target Organ Toxicity (STOT) Single Exposure	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b IARC, NTP, or OSHA. Classification criteria not met No data available
10.1 Reactivity: 10.2 Chemical stability: 10.3 Possibility of hazardous reactions: 10.4 Conditions to avoid: 10.5 Incompatible materials: 10.6 Hazardous decomposition products Section 11 11.1 Information on toxicological effects Acute toxicity Inhalation Dermal Skin corrosion/irritation Serious eye damage/eye irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity Specific Target Organ Toxicity (STOT)	No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions. Hazardous polymerization does not occur. Heat, sparks, open flame. Avoid dust formation. Strong oxidizing agents. In case of fire hazardous decomposition products may be produced: carbon monoxide, carbon dioxide, irritating smoke. Toxicological Information No data available Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons. Molten product will cause thermal burns on contact No data available Molten product will cause thermal burns on contact Classification criteria not met No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen b IARC, NTP, or OSHA. Classification criteria not met

Section 12 Ecological Information

 12.1 Toxicity 12.2 Persistence and degradability 12.3 Bioaccumulative potential 12.4 Mobility in soil 12.5 Results of PBT & vPvB assessment 	Not expected to be harmful to aquatic organisms Expected to be inherently biodegradable No data available Expected to partition to sediment and wastewater solids No data available			
Sect	tion 13 Disposal Considerations			
13.1 Disposal Follow applicable Federal, State, and loca	al regulations.			
Section 14 Transport Information				
14.1 DOT, TDG, IMO/IMDG, IATA/ICOA:	Not regulated			
Sect	tion 15 Regulatory Information			
China IECSC, Japan ENCS, Korea KECI, Ne SARA Title III, Section 302 Emergency requirements. SARA Title III, Section 311/312 Comm SARA Title III, Section 313 Toxic Chen components with known CAS numbers t Resource Conservation and Recovery hazardous waste, and is not subject to re	h the following inventories: Australia AICS, Canada DSL/NDSL, ew Zealand NZIOC, Philippines PICCS, USA TSCA y Planning: No chemicals in this material are subject to the reporting nunity Right-to-Know: None nical Release Inventory: This material does not contain any chemical that exceed the threshold (De Minimis) reporting levels. Act (RCRA): In the form delivered, this product is not considered as eporting under the Resource Conservation and Recovery Act. t known to contain any components for which the State of California has			
S	Section 16 Other Information			
EXPRESSED OR IMPLIED, INCLUDING AI PURPOSE. No statements herein are to b circumstances shall Seller be liable for ir breach of warranty, strict of liability aris sole liability for any claims shall be Buye must be confirmed by Buyer by testing for and is therefore not recommended for, u	nents. SELLER MAKES NO REPRESENTATION OR WARRANTY, NY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR be construed as inducements to infringe any relevant patent. Under no ncidental, consequential or indirect damages for alleged negligence, sing in connection with the product(s). Buyer's sole remedy and Seller's er's purchase price. Data and results are based on controlled lab work and for its intended conditions of use. The product(s) has not been tested for, uses for which prolonged contact with mucous membranes, abraded skin, ch implantation within the human body is intended.			